

## OXFORD MEMORIAL BENCHES

A complete and personal service

139 Wroslyn Road,  
Freeland,  
Witney,  
Oxfordshire OX29 8HR

Email: [info@oxmembench.co.uk](mailto:info@oxmembench.co.uk)  
Telephone: **01993 881464**  
[www.oxmembench.co.uk](http://www.oxmembench.co.uk)

### 1 Installation onto a hard-standing/slabbed area/ tarmac (*Client to provide*)



This photograph shows the best method of installing the bench. The specially made plinth should preferably be at least 300 mm longer than the bench, 75mm deep and preferably 1200 mm front to back to provide dry area for feet.

We secure the bench to the plinth using 4 specially made heavy duty galvanised angle brackets; these are screwed to the bench using stainless steel screws and the brackets are secured to the plinth using shield anchors

Anti theft stainless steel shear nuts replace 2 of the hex nuts of the shield anchors and the heads of the screws are drilled out to minimise theft risk.

Installation kit	-	£ 38	(£ 57 for 2,4m benches)
Installation charge	-	£ 40	(£ 50 for 2,4m benches)

### 2 Installation into a "grassed" area



The bench can be securely installed into a grassed area using 400mm galvanised steel anchors and stainless steel screws.

We dig 4/6 holes 400mm deep and cement the anchors in place after levelling the bench.

The drives of the screws are drilled out to minimise theft.

Please note that the legs of the bench may come into contact with moisture and maintenance of the grass may result in "trimmer" damage to the legs.

Installation kit	-	£ 38	(£ 57 for 2,4 m benches)
Installation charge	-	£ 75	(£ 100 for 2,4 m benches)

### 3 Installation onto 2 slabs



This method is an alternative to laying a full size plinth. It is not as secure a method as (2) above and should not be chosen if the risk of theft is high as the bonding of the 300mm studs into the cement cannot be guaranteed.

Soil is excavated from below the slabs and a cement mix is put into the trench: the slabs are laid and levelled up.

The bench is secured using the standard hard-standing installation kit and 300mm studs which penetrate below the slabs.

A big advantage of this method is that maintenance in the bench area is easier and the bench legs are not in contact with the soil, which will maximise the life of the bench.

Slabs and installation kit	-	£ 58	(£ 75 for 2,4 m benches)
Installation charge	-	£ 75	(£ 100 for 2,4 m benches)

Note	-	Installation kit excludes cement
	-	We reserve the right to change specification and prices without notice
	-	We cannot give any guarantee of security; a bench can always be stolen.
	-	All prices include VAT